

## LED-3214URC-1.5cd

### FEATURES

- High efficiency
- Low Power consumption
- General purpose leads
- Selected minimum intensities
- Available on tape and reel
- Pb free

### DESCRIPTIONS

- The series is specially designed for applications requiring higher brightness
- The LED lamps are available with different colors, intensities, epoxy colors, etc
- Superior performance in outdoor environment

### APPLICATIONS

- Status indicators.
- Commercial use.
- Advertising Signs
- Back lighting

### USAGE NOTES

- Surge will damage the LED
- When using LED, it must use a protective resistor in series with DC current about 20mA


### Device Selection Guide

LED Part No.	Chip		Lens Color
	Material	Emitted Color	
LED-3214URC-1.5cd	AlGaInP	Red	Water clear

### PACKAGE DIMENSIONS

#### NOTES

- Other dimensions are in millimeters, tolerance is 0.25 mm except being specified.
- Protruded resin under flange is 1.5 mm Max LED.
- Bare copper alloy is exposed at tiebar portion after cutting.



### Absolute Maximum Rating (Ta=25°C)

Parameter	Symbol	Absolute Maximum Rating	Unit
Forward Pulse Current	$I_{FPM}$	100	mA
Forward Current	$I_{FM}$	30	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	$P_D$	140	mW
Operating Temperature	$T_{opr}$	-40~+80	°C
Storage Temperature	$T_{stg}$	-40~+100	°C
Soldering Heat (5s)	$T_{sol}$	260	°C


### Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	$I_v$	800	1200	-	mcd	IF=20mA
Viewing Angle	$2\theta_{1/2}$	15	20	25	Deg	(Note 1)
Peak Emission Wavelength	$\lambda_p$	620	630	635	nm	IF=20mA
Spectral Line Half-Width	$\Delta\lambda$	15	20	25	nm	IF=20mA
Forward Voltage	$V_F$	1.9	-	2.3	V	IF=20mA
Reverse Current	$I_R$	-	-	10	μA	VR=5V

**Note:**

- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eyeresponse curve.
- $\theta_{1/2}$  is the offaxis angle at which the luminous intensity is half the axial luminous intensity.

**TYPICAL ELECTROOPTICAL CHARACTERISTICS CURVES**



**Note:**

- Above specification may be changed without notice. Factory will reserve authority on material change for above specification.
- When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. Factory assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
- These specification sheets include materials protected under copyright of factory corporation. Please don't reproduce or cause anyone to reproduce them without factory's consent.